

PRODUCT DATA SHEET

ENDURO MEDIUM GRADE

Applications: General Workshop Lubricant

- Rust Protection on stored equipment, tools, machinery
- Quadbike vehicle chassis – on beach and farm
- Frees up frozen components, padlocks, hinges, fasteners, door handles & tools.
- Electrical wiring and connections – non-conductive to 70kV-switchgear, air conditioner components, circuit boards.
- Internal motor component preservation – boat motors.
- Lubricant for drilling, cutting, machining and pressing.

Features:

- Resists wash off.
- Food Grade. NSF: H1, H2, R2
- MPI: C12 Lubricant
- Environmentally Friendly
- Biodegradable
- Non-Carcinogenic
- Non-Leaching -Non-evaporative
- Safe on rubbers and wiring.
- Non-conductive to 70kv
- Resists acids & alkalis, moisture and salt

Sizes:

- 300gsm Aerosol
- 1 Litre Tin
- 4 Litre Tin
- 20 Litre Jerry
- 200 Litre Drum

Contents:

- Natural lanolin blended with a carrier, which evaporates leaving a protective coating.



Physical Properties:

- State: Liquid-light brown colour
- Insoluble in water
- Relative vapour density (air=1): 5.3
- Lower explosive limit (%): 1.0
- Upper Explosive limit (%): 6.0
- Auto-ignition Temp (°C): >200 deg C
- Boiling Range (°C): 187-216deg C
- Specific Gravity (H20=1): 0.81-0.83@24 °C
- Vapour Pressure (kPa): 0.05kPa
- Evaporation Rate: 0.03 (BuAc=1)
- Flash Point (°C): 66
- Viscosity: [5.1@40degC](#) mm2/s
- Nonconductive point: 70Kv

Coverage:

- Approx. 8-10m2 per litre depending on the surface

Application:

- **Shake container well to mix product.**
- Apply using a trigger sprayer, garden sprayer or airless spray gun.
- The longer the time from application to use the better the surface will stay.
- On areas that need to be clean to touch – spray and wipe off excess with a rag as this will leave a thin waxy film.
- Dispose of rags away from ignitable materials.

Storage & Transport:

- NON-DANGEROUS GOODS
- **N.B Refer to Prolan SDS Enduro Medium Grade for Safe handling of Prolan products.**