

Airboy Gun For Prolan Coating

PROLAN
LANOLIN LUBRICANT

QUALITY UNDERSEALING GUN WITH 900MM HOSE TO REACH HIDDEN AREAS.

AIRBOY APPLICATION:

Clean chassis where possible before application.
Attach to air compressor with a minimum of 13 cfm.

Use the long nozzle to insert inside cavities, panels, doors
and hard to reach areas. Then withdraw through the aperture
while still depressing the trigger to coat the internal surfaces.

Clean with hot water after use as this melts the lanolin
and blows the lines clean. Suitable for application of
all Prolan products.



www.prolan.co.nz
Ph: 0800 PROLAN



Chassis coated
with Prolan – No corrosion



Bus chassis
long term rust protection

RECOMMENDED USES WITH PROLAN

- Vehicle Chassis – 4 WDs, trucks, loaders, motorhomes, buses.
- Heavy machinery applications fertiliser spreaders/loaders.
- Longterm rust protection for equipment storage outside.
- Wire rope and chain protection.
- Panelbeating applications-panelwork.
- Horticultural tractors, spray equipment.
- Wood treatment for timber decking.

FEATURES & BENEFITS OF PROLAN COATINGS

- Longlasting protection saving time on multiple reapplication.
- Increases machinery life and resale value.
- Improves COF checkout.
- Resists acids & alkalis, moisture & salt.
- Won't break down rubbers & wiring.
- Easy to apply. Resistes wash off.
- Environmentally friendly and biodegradable.
- Food Grade. NSF H1 MPI: C12

APPLICATION

Where possible remove any dirt, scale or other surface coating before applying Prolan and leave overnight or longer. Applications can be recoated in 12-24 mth intervals depending on the situation.

N.B Cold water blasting will not remove Prolan coating.
Prolan cleaner available to remove existing coatings

Like us on facebook!  Prolan New Zealand